TOWN OF NEW WINDSOR

HIGHWAY DEPARTMENT

555 UNION AVENUE NEW WINDSOR, NEW YORK 12553-6196 Telephone: (845) 564-6660 Fax: (845) 564-5102

DRIVEWAY CONSTRUCTION SPECIFICATIONS

- 1. Access from driveway to Town roadway will have acceptable sight distance in both directions as approved by the Town Superintendent of Highways.
- 2. Centerline of driveway shall be perpendicular to Town Roadway and a minimum of fifteen (15') feet from property line.
- 3. Paved area: Shall extend from edge of pavement to Town Roadway right-of-way line, Minimum ten (10') foot depth.

Minimum width at Town roadway edge of pavement shall be twenty (20') feet, tapering to a minimum of ten (10') foot width at ten (10') foot depth.

Paved area shall have a minimum slope of eight (8%) percent (1 in/1 ft) away from Town Roadway for a minimum distance of four (4') feet. Grading shall be to the satisfaction of the Town Superintendent of Highways and the Town Engineer prior to surfacing such driveways.

- 4. Pavement Application: 3" minimum asphalt concrete wearing coarse6" minimum item #4 subbase coarse
- 5. Where required by the Town Superintendent of Highways, a culvert pipe shall be provided at the driveway, with the pipe size and material to be as acceptable to the Superintendent. Pipe size shall not be less than fifteen (15") inches diameter.